



## ESD 15 INFLOW NOZZLE

### FRESH WATER INLET ARMATURE FE 1040 T

For undisturbed satisfaction in clean fountain pools and ponds.

Filtered water is fed back into the pool through stainless steel and bronze inflow nozzles. Direction of flow can be changed by adjusting the nozzle.

Fresh water inlet armatures are used to fill the pool and for top-up feed of evaporated water from the public drinking water network. The water-level can be adjusted from 100 to 1000 mm.

<b>Inflow nozzle</b>	<b>FE 10/1040 T</b>	<b>ESD 15 E</b>				
<b>Dimensions (LxWxH) [mm]</b>	100x100x1110	Ø101x31				
<b>Thread</b>	1"	1 1/2"				
<b>Material</b>	tombac/brass	stainless steel				
<b>Weight [kg]</b>	2.3	0.3				
<b>Order no.</b>	<b>55840</b>	<b>53086</b>				

<b>Floor/wall transition</b>	<b>BWD 10-175 E</b>	<b>BWD 15-175 E</b>	<b>BWD 20-175 E</b>	<b>BWD 40-175 E</b>		
<b>Dimensions (LxWxH) [mm]</b>	100x100x175	100x100x175	150x150x175	200x200x175		
<b>Thread</b>	1"	1 1/2"	2"	4"		
<b>Material</b>	stainless steel	stainless steel	stainless steel	stainless steel		
<b>Weight [kg]</b>	0.6	1.1	2.0	3.6		
<b>Order no.</b>	<b>51141</b>	<b>51142</b>	<b>51143</b>	<b>52790</b>		

